

ISOPIPE TC Pipes (UV PLUS)



EXTERNAL PIPE DIAMETER			THICKNESS & DIMENSION OF INSULATION									
Fe Inch	Cu		9mm 3/8"		13mm 1/2"		19mm 3/4"		25mm 1"		30mm 1 1/4"	
	mm	Inch	Φ	m	Φ	m	Φ	m	Φ	pcs	Φ	pcs
---	Φ 6	1/4"	√	270								
---	Φ 10	3/8"	√	190	√	130	√	70				
---	Φ 12	---	√	180	√	120	√	70				
1/4"	Φ 15	---	√	140	√	100	√	50	√	40	√	30
3/8"	Φ 18	---	√	130	√	90	√	50	√	40	√	30
1/2"	Φ 22	7/8"	√	100	√	70	√	44	√	30	√	24
3/4"	Φ 28	1 1/8"	√	80	√	60	√	40	√	26	√	24
1"	Φ 35	1 3/8"	√	70	√	44	√	30	√	24	√	18
1 1/4"	Φ 42	1 5/8"	√	60	√	36	√	28	√	22	√	16
1 1/2"	Φ 48	1 7/8"	√	40	√	30	√	22	√	18	*	14
---	Φ 54	2 1/8"	√	36	√	26	√	20	√	16	√	12
2"	Φ 60	2 3/8"	√	36	√	24	√	16	√	12	*	10
---	Φ 64	2 1/2"	√	32	√	22	√	16	√	12	*	10
2 1/2"	Φ 76	3"	√	32	√	20	√	14	√	10	*	10
3"	Φ 89	3 9/16"	√	20	√	16	√	12	√	8	*	8
---	Φ 101	4"	√	16	√	16	√	8	*	8		
3 1/2"	Φ 108	4 1/4"	√	16	√	16	*	8	*	6		
4"	Φ 114	4 9/16"	√	12	√	16	√	8	√	6		
5"	Φ 139	5 1/2"	*	10	√	8	√	6	√	4		
Thickness Tolerance			± 1,5 mm		± 1,5 mm		± 2,0 mm		± 2,0 mm		± 2,0 mm	

- Standard length for ISOPIPE TC UV PLUS is 95 cm (± 5 cm).
- Standard carton size is 210x41x27 cm.
- Up to 5% of total carton content may be in 1 meter length.
- Dimensions marked with a * should be consulted for price and availability.

ISOPIPE TC System (UV Plus)

- ✓ Protection Thickness: aprx. 125µm
- ✓ Layers: PET (Polyester) transparent film - Aluminium foil PE (Polyethylene)