

ISOPIPE HT Pipes (UV)

Synthetic rubber installation with UV protection.



EXTERNAL PIPE DIAMETER				INTERNAL DIAMETER min - max	THICKNESS & DIMENSION OF INSULATION					
Fe	Cu		PP		9mm 3/8"		13mm 1/2"		19mm 3/4"	
Inch	mm	Inch			Φ	m	Φ	m	Φ	m
---	Φ 6	1/4"		7,0 - 8,0	*	270	*	156	*	84
---	Φ 10	3/8"		11,0 - 12,0	√	190	√	130	√	70
---	Φ 12	---		13,0 - 14,0	√	180	√	120	√	70
1/4"	Φ 15	---		16,0 - 17,0	√	140	√	100	√	50
3/8"	Φ 18	---		19,0 - 20,0	√	130	√	90	√	50
1/2"	Φ 22	7/8"		23,0 - 24,0	*	100	*	70	*	44
---	Φ 25	1"	Φ 25	26,0 - 27,0	√	80	√	60		
3/4"	Φ 28	1 1/8"		29,0 - 30,0	√	80	√	60	√	40
1"	Φ 35	1 3/8"		36,0 - 37,0	√	70	√	44	√	30
1 1/4"	Φ 42	1 5/8"	Φ 40	43,0 - 44,0			√	36	√	28
Thickness Tolerance					± 1,5 mm		± 1,5 mm		± 2,0 mm	

- Dimensions marked with a * should be consulted for price and availability
- Standard length for ISOPIPE HT UV is 2 m (± 1.5 %)