

ISOPPIPE HT System (Regular, UV PLUS, HD)

Pre-slanted cut elastomeric sheets for large bore pipes.



OD mm	OD Inch	THICKNESS & DIMENSION OF INSULATION				
		13mm 1/2"	19mm 3/4"	25mm 1"	32mm 1 1/4"	40mm 1 9/16"
		Φ	Φ	Φ	Φ	Φ
Φ 89	3"	√	√	√	√	√
Φ 101		√	√	√	√	√
Φ 108		√	√	√	√	√
Φ 114	4"	√	√	√	√	√
Φ 127		√	√	√	√	√
Φ 133		√	√	√	√	√
Φ 139	5"	√	√	√	√	√
Φ 152		√	√	√	√	√
Φ 156		√	√	√	√	√
Φ 160		√	√	√	√	√
Φ 168	6"	√	√	√	√	√
Φ 203		√	√	√	√	√
Φ 219	8"	√	√	√	√	√
Φ 254		√	√	√	√	√
Φ 273	10"	√	√	√	√	√
Φ 305		√	√	√	√	√
Φ 323	12"	√	√	√	√	√
Φ 356	14"	√	√	√	√	√
Φ 406	16"	√	√	√	√	√
Φ 457	18"	√	√	√	√	√
Φ 508	20"	√	√	√	√	√
Thickness Tolerance		± 1,5mm	± 1,5 mm	± 2,0 mm	± 2,0 mm	± 2,0 mm



- Standard length 1 meter ($\pm 1.5\%$)
- Standard carton size is 104x51x62 cm
- ISOPPIPE HT SYSTEM can also be offered with SLIT & SEAL tapes, including two self-adhesive and one overlap tape.

ISOPPIPE HT System (UV PLUS)

- ✓ Protection Thickness: aprx. 125µm
- ✓ Layers: PET (Polyester) transparent film - Aluminium foil PE (Polyethylene)

ISOPPIPE HT System (HD)

- ✓ Protection Thickness: aprx. 230µm
- ✓ Layers: Transparent film - Aluminium glossy - PVC FR (Flame Retardant)