

DECLARATION OF PERFORMANCE**No. 1020 - CPD - 010030388-08****Unique identification code of the product-type:****ISOPipe ISOSOL TC****Intended use/es:**

*ThIBELL : Flexible Elastomeric Foam,
intended to be
used as Thermal insulation for building
equipment
and industrial installations.*

Manufacturer:

*Isopipe SA, 26 Nafpliou str., 144 52
Metamorfosi, Athens, Greece
Plant: 68° km Nat. Road Athens-Lamia,
34100 Ritsona, Halkida, Greece*

System/s of AVCP:**3****Harmonised standard:****EN 14304:2009+A1:2013****Notified body:****NB 1020****Declared performance/s:**

| Essential characteristics | Performance |
|----------------------------------|--------------------------------------------------------------------------------------------|
| <i>Thermal Conductivity</i> | <i>-20°C - 0.031 W/mk 0°C - 0.033 W/mk 20°C - 0.035 W/mk 30°C - 0.036 W/mk</i> |

Rebuild the future!

| Reaction To Fire | Tubes: EL |
|---------------------------------------------------------------|------------------------------------------------------------------------------|
| Durability of thermal resistance against ageing/degradation | Dimensional stability (1) Minimum service temperature ST(-) -50 (=-50 °C) |
| Durability of thermal resistance against high temperature | Maximum service temperature ST(+) 110 (=110 °C) |
| Durability of reaction to fire against high temperature | (2) |
| Durability of reaction to fire against ageing / degradation | (2) |
| Compressive strength | (3) |
| Water permeability | NPD |
| Water vapour permeability / Water vapour diffusion resistance | 10.000 |
| Rate of release of corrosive substances | Cl-<300ppm |
| Acoustic (absorption) index | NPD |
| Release of dangerous substances to the indoor environment | (4) |
| Continuous glowing combustion | (4) |

1) The thermal conductivity of FEF does not change with time.

2) The fire performance of FEF does not change with time.

3) Compressive strength is not applicable for FEF products.

4) European test methods are under development

NPD = No Performance Determined.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Ritsona, 08/01/25

Signed for and on behalf of the manufacturer by:

Markati Athanasia,

Quality Assurance Manager
ISOPipe S.A.
 Head Office: 26, Nafpliou & Daskalogianni str.
 144 52 ATHENS - GREECE - TEL: +30 210 2828603
 FACTORY: 68 KM NAT. Rd Athens-Lamia, 34100 Ritsona-Halkida
 TEL.: +30-22620-71851
 GREECE - VAT REG No: EL 094460772