

DECLARATION OF PERFORMANCE

No. 1020 - CPD – 010030388

Unique identification code of the product-type:

ISOPIPE UV PLUS HT-HF Tubes and Sheets

Intended use/es:

ThIBELL : Flexible Elastomeric Foam, intended to be used as Thermal insulation for building equipment and industrial installations.

Manufacturer:

**Isopipe SA, 26 Nafpliou str.,144 52 Metamorfofi, Athens, Greece
Plant: 68° km Nat. Road Athens-Lamia, 34100 Ritsona, Halkida, Greece**

System/s of AVCP:

3

Harmonised standard:

EN 14304:2009+A1:2013

Notified body:

NB 1020

Declared performance/s:

Essential characteristics	Performance
<i>Thermal Conductivity</i>	0°C - 0.040 W/mk 40°C - 0.045 W/mk
<i>Reaction To Fire</i>	Tubes: EL Sheets: E

Rebuild the future!

<i>Durability of thermal resistance against ageing/degradation</i>	<i>Dimensional stability (1)</i>
<i>Durability of thermal resistance against high temperature</i>	<i>Minimum service temperature ST(-) -50 (= -50°C)</i>
<i>Durability of reaction to fire against high temperature</i>	<i>Maximum service temperature ST(+) 150 (=110 °C)</i>
<i>Durability of reaction to fire against ageing / degradation</i>	(2)
<i>Compressive strength</i>	(3)
<i>Water permeability</i>	NPD
<i>Water vapour permeability / Water vapour diffusion resistance</i>	4000
<i>Rate of release of corrosive substances</i>	NPD
<i>Acoustic (absorption) index</i>	NPD
<i>Release of dangerous substances to the indoor environment</i>	(4)
<i>Continuous glowing combustion</i>	(4)

1) The thermal conductivity of FEF does not change with time.

2) The fire performance of FEF does not change with time.

3) Compressive strength is not applicable for FEF products.

4) European test methods are under development

NPD = No Performance Determined.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Ritsona, 08/01/25

Signed for and on behalf of the manufacturer by:



Markati Athanasia,

Quality Assurance Manager