

ISOTAPE®

Self-Adhesive Insulation Tape



Interior Use

SOLAR Polymer



Exterior Use

PVC



Exterior Use

UV PLUS Pet-Al-Pe



Exterior Use

Properties	Self-Adhesive Insulation Tape	SOLAR Polymer	PVC	UV PLUS Pet-Al-Pe
Length	10m & 15m	10m & 25m	33m	10m & 25m
Width	50mm			
Support	PES/ PVA scrim			
Interliner	Yellow 90g / m ² double sided siliconized		Yellow 90g / m ² double sided siliconized	
Adhesive Weight	60g/ m ²		70g/ m ²	
Adhesive Thickness	60µm		70µm	
Upper Temperature (°C)	+90°C		+100°C	
Lower Temperature (°C)	-40°C			
Adhesive Strength (based on AFERA 5001)	min 18 N/ 25mm	22 N/ 25mm	40 N/ 25mm	22 N/ 25mm
Colour	Black	Silver, Black & White	Black & White	Aluminum

The mentioned values are these which have been measured in our laboratory, under typical conditions. They can be modified without prior notice. You are kindly requested to assert their validity before any special use.

ISOPIPE® S.A.

www.isopipe.eu

GREECE
 Head Office:
 Nafpliou & Daskalogianni
 144 52 Metamorfofi Attikis
 T.: +30 210 28 28 603
 F.: +30 210 28 19 210
 E.: export@isopipe.gr

Plant:
 73rd km Nat. Road Athens - Lamia
 341 00 Ritsona Halkida
 T.: +30 22620 89 800
 F.: +30 22620 72 006
 E.: export@isopipe.gr

SPAIN
Barcelona:
 C/ Costa l Deu 71 - 79 (esq. C/ Tamari) 08205, Sabadell, Barcelona, España

Madrid:
 Calle Pedro Duque, 5,
 Poligono Industrial GITESA,
 28.814- Daganzo de Arriba (Madrid),
 Madrid Community

T.: +34 93 879 1195
 F.: +34 93 879 1313
 E.: pedidos@isopipe.es

UNITED KINGDOM
Head Office:
 178 Seven Sisters Road
 London N7 7PX
 United Kingdom

Warehouse:
 Airfield Industrial Estate Warboys,
 Huntingdon
 Cambridgeshire PE28 2SH
 United Kingdom

T.: +30 210 28 28 603
 E.: orders@isopipe.eu