

Type of Material	Self-adhesive aluminum covering tape for hygienic and internal applications composed of five layers and protected by a siliconized paper release liner.
Product Range	Available in • Standard width: 50 mm. • Standard length: 25 m.
Fields of Application	Sealing of longitudinal and transversal joints of thermal insulation for refrigeration, air conditioning and heating & plumbing services in commercial, industrial and domestic applications.
Colour	Silver.
Storage & Shelf Life	Material shall be stored indoors, in clean and dry conditions, away from direct sunlight. Self-adhesive tapes: 1 year.

Properties	Technical Data	Test Methods
Thickness of film	HP Film*: 60 µm Silicone Release Liner: 85 µm	DIN 53370
Film Weight	154 gr/m ²	ASTM D646
Tensile Strength	50N/ 25mm	ASTM D3759
Elongation	20%	ASTM D3759
Reflectivity of Foil Surface	95%	
Operating Temperatures (°C)	HP Film*: -35°C (-31°F) to +120°C (248°F)	

Storage Conditions

Material shall be stored indoors, in clean and dry conditions, away from direct sunlight and sources of heat. Products should remain in their original packaging until installation.

The mentioned values are those measured in our laboratory under typical conditions. They may be modified without prior notice. Customers are kindly requested to verify their validity before any specific or special application.